

# Zehnder Quaro

## Ausführung lackiert

Modell	H <sup>2)</sup> mm	L mm	Wärmeleistung				Zuordnung Heizstab Watt
			75/65/20 °C <sup>1)</sup>	70/55/24 °C	55/45/24 °C	55/45/20 °C	
			Watt	Watt	Watt	Watt	
QA-100-030	971	300	299	216	133	159	300
QA-140-030	1403	300	421	305	188	225	300
QA-180-030	1835	300	543	394	243	290	300
QA-100-045	971	450	420	304	187	223	300
QA-140-045	1403	450	590	428	264	315	500
QA-180-045	1835	450	761	552	341	406	600
QA-100-060	971	600	533	387	239	284	300
QA-140-060	1403	600	749	543	335	400	600
QA-180-060	1835	600	966	700	432	515	900

## Ausführung verchromt

Modell	H <sup>2)</sup> mm	L mm	Wärmeleistung				Zuordnung Heizstab Watt
			75/65/20 °C <sup>1)</sup>	70/55/24 °C	55/45/24 °C	55/45/20 °C	
			Watt	Watt	Watt	Watt	
QAC-100-030	971	300	189	135	81	97.2	-
QAC-140-030	1403	300	270	192	115	139	300
QAC-180-030	1835	300	348	248	149	179	300
QAC-100-045	971	450	267	191	115	138	300
QAC-140-045	1403	450	381	272	164	197	300
QAC-180-045	1835	450	491	350	210	253	300
QAC-100-060	971	600	341	244	148	177	300
QAC-140-060	1403	600	486	347	209	251	300
QAC-180-060	1835	600	627	448	270	324	600

## Ausführung Edelstahl

Modell	H <sup>2)</sup> mm	L mm	Wärmeleistung				Zuordnung Heizstab Watt
			75/65/20 °C <sup>1)</sup>	70/55/24 °C	55/45/24 °C	55/45/20 °C	
			Watt	Watt	Watt	Watt	
QAI-100-030	971	300	229	164	100	120	-
QAI-140-030	1403	300	321	230	140	168	300
QAI-180-030	1835	300	415	298	181	217	300
QAI-100-045	971	450	321	231	141	169	300
QAI-140-045	1403	450	450	324	197	236	300
QAI-180-045	1835	450	581	418	255	305	300
QAI-100-060	971	600	407	293	179	214	300
QAI-140-060	1403	600	572	412	251	301	300
QAI-180-060	1835	600	738	531	324	388	600